





RELEASED
67.04.24 UP
PER ECN 889

UNDER REVIEW

11.06.13



D2940-1

- 1) MATERIAL: 17-4 PH STAINLESS STEEL
HEAT TREAT TO H900 CONDITION
(900°F FOR 1 HR, AIR COOL)
MIN UTS = 170 KSI (38 HRC)
- 2) IDENTIFY WITH DART LOGO AND PART NUMBER IN THIS AREA
WITH 0.125 HIGH LETTERING 0.010-0.020 DEEP
- 3) BREAK ALL UNMARKED SHARP EDGES 0.010 TO 0.020
- 4) PART IS SYMMETRIC ABOUT CENTERLINE
- 5) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED
- 6) ALL DIMENSIONS ARE IN INCHES
- 7) FINISH: POWDER COAT WHITE (REF 4.3.5.2) PER DART QSI 005 4.3
PRIME INSIDE SURFACE AS SHOWN PER DART QSI 005 4.2

COPYRIGHT © 2001 BY DART AEROSPACE LTD.

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL
AND IS SUPPLIED ON THE EXPRESS CONDITION
THAT IT IS NOT TO BE USED FOR ANY PURPOSE
OR COPIED OR COMMUNICATED TO ANY OTHER
PERSON WITHOUT WRITTEN PERMISSION FROM
DART AEROSPACE LTD.

B	07.03.16	UPDATE PER NCR 642, PRIME INSIDE
A	01.01.10	NEW ISSUE
DESIGN	9P	DRAWN BY PH
CHECKED	TH	APPROVED
DATE	07.03.16	TITLE
		03.250 SUPPORT
		SCALE 1:2
		REV. B SHEET 1 OF 1

DART DART AEROSPACE LTD.
HAWKESBURY, ONTARIO, CANADA

DRAWING NO.
D2940

TITLE
03.250 SUPPORT

REV. B
SHEET 1 OF 1

SCALE
1:2